

Henchman Barrow Trailer

User Manual

Safety in Operation

These symbols are displayed on the lid. Please take time to understand what these symbols mean.



a. b. c. d.

- a. This is a very large and robust Barrow. There is a maximum weight restriction of 400kg.
- b. If in doubt, please refer to the User Manual, if you are at all unsure about any operation procedures.
- c. Not to be used by children. Do not put children in the Barrow and push them about.
- d. Always stop and think before using the Barrow-Trailer on sloping ground or moving heavy loads.

Assembly

1. Remove the Barrow-Trailer from the cardboard packaging and rest it on its wheels and feet on the ground.
2. The Barrow-Trailer will be packaged with wheels in the Trailer position (Axle Position A).
3. To move the axle into the Barrow usage position (Axle position C), turn the Barrow upside down and pull out one of the large clips which secures the wheel on to the axle. Slide the washer, wheel and spacer off the axle. Walk round the other side of the Barrow and pull the wheel and axle right out of the axle position A in the Barrow.
4. Slide the axle into the axle position of your choice and re-assemble the wheels, washers, spacers and R clips. Axle position C is the best suited position to use as a Barrow. This is because the weight of the Barrow and its load is balanced over the axle. This will take any unnecessary weight away from the handles. (Please note: If you were to use the Barrow with the axle in position A, then the weight will not be balanced over the axle and the handles would feel a lot heavier.)
5. Turn the Barrow the right way up and you are now ready to use.

Accessories

Extension sides – The extension sides give you the option and the capability of increasing the capacity of the Barrow. The extension sides will be flat packed so take the extension sides out of its packaging and open it up and place it inside the Barrow, resting it on the ledge, half way down the inside of the Barrow.

Make sure you have got the extension sides the right way up by noting that you have the top edge with the black elastic, resting out of the top of the Barrow. Pull the black elastic around one of the three large hooks located on each side of the Barrow (6 in total) which will fix the extension sides in place.

You will notice that one side of the extension sides can be opened up and folded down. This will help with loading the Barrow, so you will not have to lift your spade higher than is necessary. Once you have closed the flap, wrap the black elastic all the way around the extension sides which will get rid of any excess elastic.

Net – The net is designed to locate all the loose and unstable loads i.e. grass cuttings or leaves. Place the net over the Barrow and by pulling it tight; locate the net onto the 3 hooks on each side of the Barrow. (6 in total.)

Plant Tray- The Plant Tray is designed to give you a flat base to work from, so you can transport plant pots etc safely and easily in side the Barrow. Place the Plant Tray inside the Barrow with the smooth side facing down and the rough surface facing up. The Plant Tray will rest on the ledge half way down the inside of the Barrow.

Draw Bar – The draw bar is in 2 parts – Barrow part and Tractor part. Identify the Tractor part by the jaws or ball & hitch connection.

1. Turn the Barrow upside down and prepare to put the axle into position A.
2. Connect the Barrow part ensuring that the axle passes through the tube at the end, and that the spring loaded bolt is secure in the hole beneath the Barrows' handles.
3. Re-assemble the wheels, spacers, washers and R clips and turn the Barrow the right way up.
4. Slide the Tractor part with the kink facing down wards, into the Barrow part and secure with 12mm pin and R clip provided.

Maintenance

The only maintenance required is to regularly grease the axle.